



MASTER Series 410 SRS/SRC

Solid and reliable scales, for rough use year after year

SWISS DESIGN 

Ease of use

Simple uncomplicated operation is the first requirement in industry for the smooth functioning of your balance. Clear user guidance from the display guarantees correct entering of commands.



- Rugged Scale with stainless steel platform
- Choice of two terminals
- Practical and user-friendly
- LC display with backlight
- Battery operation
- RS232 interface
- Units kg and lb
- 2 years warranty

Platforms

Strain gauge platform SRC stainless steel IP 67

Strain gauge platform SRS steel painted IP 65



Terminal SRD, ABS or stainless steel IP 67

- Large LC display with backlight
- Battery operation
- Units kg and lb
- Check weighing program



Terminal SRM, ABS or stainless steel IP 67

- LC display with backlight
- Battery operation
- Counting, units kg and lb
- Direct: - ID and date settings
 - tare entry
 - reference weight entry for counting

Precisa

■ The Balance of Quality ■

supplyLAB
www.supplylab.pt



Terminal SRD



Model	Type approval	Dimensions WxLxH (mm)	Net weight	Protection
SRD ABS	EC / OIML, III	240 x 160 x 120	1.6 kg	IP42
SRD SST	none	280 x 190 x 180	3 kg	IP67

Terminal SRM



Model	Type approval	Dimensions WxLxH (mm)	Net weight	Protection
SRM ABS	EC / OIML, III	240 x 160 x 120	1.6 kg	IP42
SRM SST	none	280 x 190 x 180	3 kg	IP67

Platform steel painted

Model	Capacity	Readability	Repeatability	Linearity	Pan Size (mm)	Response time	Verification scale interval
SRS 75K	75 kg	5 g	5 g	5 g	500 x 400	2 s	50 g
SRS 150K	150 kg	10 g	10 g	10 g	500 x 400	2 s	50 g
SRS 300K	300 kg	20 g	20 g	40 g	500 x 400	2 s	100 g

Dimensions (WxLxH) 500x400x135 mm

Protection IP 65

* technical data in connection with terminal SRD or SRM

Net weight 14.7 kg

Sensitivity drift (10...30°C) 14 ppm / °C

Platform stainless steel

Model	Capacity	Readability	Repeatability	Linearity	Pan Size (mm)	Response time	Verification scale interval
SRC 75K	75 kg	5 g	5 g	5 g	500 x 380	2 s	50 g
SRC 150K	150 kg	10 g	10 g	10 g	500 x 380	2 s	50 g

Dimensions (WxLxH) 500x380x105 mm

Protection IP 67

* technical data in connection with terminal SRD or SRM

Net weight 8.3 kg

Sensitivity drift (10...30°C) 30 ppm / °C

Options	410	Accessories	410
Set for EC / OIML verification, not verified, available only for balances with EC (/ OIML) Type approval	350-8680	Wall bracket for displays SRD ABS and SRM ABS	350-8626
		Post for rear mounted display to platform SRS	350-8627
		Post for rear mounted display to platform SRC	350-8629
		Printer CBM910 230V - with cable and paper roll	350-8381
		Printer CBM910 115V - with cable and paper roll	350-8382
		Paper roll for Printer CMB910	350-8366
		Ribbon for Printer CBM910	350-8367
		Data cable DB9 Female / DB9 Female 1.5m (PC)	350-8674
		Data cable DB9 Female / DB25 Male 1.5m (Printer)	350-8675

supplyLAB

www.supplylab.pt
geral@supplylab.pt

Cacém Park - Edifício 9
Estrada de Paço de Arcos nº88
2739-512 Aqualva Cacém
T +(351) 21 4278700
F +(351) 21 4278709

Precisa
■ The Balance of Quality ■

Precisa Gravimetrics AG
Moosmattstrasse 32
CH-8953 Dietikon

Tel. 0041 (0)44 744 28 28
Fax 0041 (0)44 744 28 38
www.precisa.com; info@precisa.ch

