Thermo Scientific Heraeus® Labofuge® 200 Centrifuge

The functional Thermo Scientific Heraeus Labofuge 200 is ideal for use in medical practices, clinical and small laboratories and as a stand-by unit in large laboratories.

Easy to use

- Accomodates a wide range of the most popular medical tubes
- Maintenance-free
- Safe



Set the required speed and the required time. With the "start" button, repeat runs can easily be recalled.



Maintenance-free

Our Heraeus Labofuge 200 is equipped with a brushless motor, so there is no need to replace carbon brushes. Besides saving time and money, this also ensures clean operating conditions.

Accessories

Made of impact resistant, fiberglass reinforced polyamide, our autoclavable rotor offers high stability and outstanding run characteristics. It is easily removed for cleaning in the laboratory washing machine. An extensive range of adapters permits centrifugation of all standard 5, 7, 10 and 15 ml tubes, including the popular "Monovette", "Vacutainer" and "VenoJect" blood collection tubes.

Safety

Our Heraeus Labofuge 200 complies with international safety standards and is equipped with a lid lock, lid interlock and a steel armoured guard ring.

Functions

The microprocessor controlled Heraeus Labofuge 200 is equipped with bright digital displays and touch-pad keys for quick and easy setting of speed and run-time. To repeat a run, simply press the start key. It is also designed with a user friendly self diagnosis system which indicates faults directly on the display.



Cacém Park - Edifício 9 Estrada de Paço de Arcos nº88 2739-512 Agualva Cacém T +(351) 21 4278700 F +(351) 21 4278709



Thermo Scientific Heraeus Labofuge 200

| Specifications | Heraeus Labofuge 200 (230V version) | Heraeus Labofuge 200 (110-120V version) | | | |
|-----------------------------|---|---|--|--|--|
| Description | Microprocessor controlled table top centrifuge | Microprocessor controlled table top centrifuge | | | |
| Maximum speed rpm | 5300 | 5000 | | | |
| Minimum speed rpm | 1600 | 1600 | | | |
| Maximum RCF x g | 3030 | 2600 | | | |
| Minimum RCF x g | 270 | 270 | | | |
| Maximum capacity ml | 12 x 15 (glass) | 12 x 15 (glass) | | | |
| Controller | Microprocessor controller for time and speed | Microprocessor controller for time and speed | | | |
| Drive | Brushless induction motor, microprocessor controlled | Brushless induction motor, microprocessor controlled | | | |
| Runtime | 1-99 min. and continuous operation (Hold) | 1–99 min. and continuous operation (Hold) | | | |
| Program memory | Stores values last entered, unlimited | Stores values last entered, unlimited | | | |
| Safety | Lid lock and lid interlock, steel armoured guard ring | Lid lock and lid interlock, steel armoured guard ring | | | |
| Design | Fiberglass reinforced polyamide housing with high noise and vibration insulation properties | | | | |
| Dimensions (HxWxD) mm/inch | 240 x 284 x 375/9.5 x 11.2 x 14.8 | 240 x 284 x 375/9.5 x 11.2 x 14.8 | | | |
| Weight (incl. rotor) kg/lbs | Approx. 10.7/23.5 | Approx. 10.7/23.5 | | | |
| Power consumption W | 65 | 65 | | | |

| Ordering Information | Heraeus Labofuge 200 (230V version) | Heraeus Labofuge 200 (110-120V version) |
|----------------------|-------------------------------------|---|
| Catalog Number | 75003630 | 75003631 |



Thermo Scientific Heraeus Labofuge 200 Rotors and Accessories

| HFP 5.15 Angle Rotor | | | |
|-----------------------|---------------|-------------------|--|
| Description | 230 V version | 110–120 V version | |
| Catalog number | 75003760 | 75003760 | |
| Max. speed rpm | 5300 | 5000 | |
| Max. RCF x g | 3030 | 2600 | |
| Max. capacity ml | 12 x 15 | 12 x 15 | |
| Max. radius cm/inch | 9.65 /3.8 | 9.65 /3.8 | |
| Acceleration time sec | 40 | 40 | |
| Braking time sec | 45 | 45 | |

Accessories for fixed angle rotor

The adapter set (75003227) included with the centrifuge contains a complete set of adapters: 12 of each yellow, cream, and rubber distance pads.

| Tube Volume (ml) Type of Tube | | Dimension (mm) Diam. Length | | Tubes Per Rotor | Type of Adapter required | Adapter Order No. |
|-------------------------------|------------------------|--------------------------------|-------|-----------------|--------------------------|------------------------------------|
| 7 | Glass tubes (DIN) | 12 | 100 | 12 | yellow | 75003227 |
| 15 | Glass tubes (DIN) | 16 | 100 | 12 | 4) | _ |
| 3–5 | VenoJect® II (Terumo®) | 13 | 75 | 12 | cream + rubber pad | 75003227 75003266 |
| 7 | VenoJect II (Terumo) | 13 | 100 | 12 | yellow | 75003227 |
| 9–10 | VenoJect II (Terumo) | 16 | 100 | 12 | sleeves | 75003763 ³⁾ |
| 3–5 | Vacutainer® (BD™) 2) | 13 | 75 | 12 | cream + | 75003227 |
| | V | 10 | 100 | 10 | rubber pad | 75003266 |
| | Vacutainer (BD) 2) | 13 | 100 | 12 | yellow | 75003227 |
| 1 | Vacutainer (BD) | 16 | 75 | 12 | sleeves + rubber pad | 75003763 ³⁾ 75003266 |
| 10 | Vacutainer (BD) 2) | 16 | 100 | 12 | 4) | _ |
| 15 | Vacutainer (BD) | 16 | 125 | 6 | 4) | _ |
| 4 | Sarstedt® Monovette® | 11.5 | 83.5 | 12 | cream | 75003227 |
| 5 | Sarstedt Monovette | 13 | 90 | 12 | cream | 75003227 |
| 7.5 | Sarstedt Monovette | 15 | 92 | 12 | 4) | _ |
| 9 | Sarstedt Monovette | 16.5 | 92 | 6 | rubber pad | 75003762 |
| 12 (Urine) | Sarstedt Monovette | 16.5 | 101.5 | 6 | 4) | _ |
| Urine tubes | BD™, Terumo® | 16 | 100 | 12 | sleeves | 75003763 ³⁾ |

¹⁾ included with centrifuge ²⁾ tube incl. Hemoguard cap ³⁾ included with rotor ⁴⁾ not necessary

North America: USA/Canada +1 866 984 3766

www.thermo.com/centrifuge

Europe: Austria +43 1 801 40 0, Belgium +32 2 482 30 30, France +33 2 2803 2000, Germany national toll free 08001-536 376, Germany international +49 6184 90 6940, Italy +39 02 02 95059 434-254, Netherlands +31 76 571 4440, Nordic countries +358 9 329 100, Russia/CIS +7 (812) 703 42 15, Spain/Portugal +34 93 223 09 18, Switzerland +41 44 454 12 12, UK/Ireland +44 870 609 9203 Asia: China +86 21 6865 4588 or +86 10 8419 3588, India +91 22 6716 2200, Japan +81 45 453 9220, Other Asian countries +852 2885 4613 Countries not listed: +49 6184 90 6940 or +33 2 2803 2000

BRO-LECF-LABO200-0208

