



ROTOR SPECIFICATIONS

Type	Swinging Bucket
Material	Titanium
Capacity	4 x 7.0 mL
Maximum Speed	50,000 rpm
Tube Dimensions Ø x L	13 x 51 mm
Angle	180°
K Factor	76.6
Net Weight	1.8 kg/3.9 lbs
Warranty	5 years

	RCF	RADIUS
Maximum	252,721 xg	90.5 mm
Average	185,701 xg	66.5 mm
Minimum	118,681 xg	42.5 mm

ROTOR AND ACCESSORIES ORDERING INFORMATION

S50-ST Rotor Package includes:

Description	Cat. No.
S50-ST Rotor ¹	45541
PA Thin-Walled Tubes (qty. 1 pkg. of 50)	S309146A
Bucket O-ring (qty. 8)	8062220
Bucket Stand	45312
Bucket Cap Wrench	45277
Rotor Stand	45275
Lubricant	61556
Vacuum Grease	65937
Instruction Manual	45735

Accessories:

Description	Cat. No.
Spare Buckets (qty. 4)	46107

LABWARE ORDERING INFORMATION

Tube Vol. (mL)	Vol. Fill (mL)	Description	Cat. No.	Qty. /Pkg.	Tubes /Rotor	Max. Speed (rpm)	Max. RCF (xg)	Dims ØxL (mm)	REQUIRED TUBE CLOSURES, ADAPTERS, TOOLS & ACCESSORIES			
									Type	Cat. No.	Qty. /Pkg.	Description
7.0	7.0	PET Tube Assembly	S309168A	50	4	50,000	252,721	16 x 52	—	—	—	—
7.0	7.0	PA Tube Assembly	S309146A	50	4	50,000	252,721	16 x 52	—	—	—	—

¹ Rotor compatible only with Thermo Scientific Sorvall MTX-150 and MX Series micro-ultracentrifuges.

© 2010 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

For more information, please visit
www.thermoscientific.com/rotors.