



SPARK-PROOF 700



Characteristics

Structure	White or Stainless steel 18/10 int. + ext.
Insulation thickness	60 (polyur. mm)
Doors number	1
Door type	Fully Insulated
Refrigeration type	Ventilated
Refrigerant type	R404A
Temperature range	+2° +15°
Temperature control/adjustment	ECT-F Control® : with Hi/Low Temp. alarm, door ajar, ON/OFF w/password
Defrosting type	Auto
Voltage	230V/1/50Hz
Capacity (LT)	700
Shelves nr.	suggested 3
Width (cm)	72
Depth (cm)	80
Height (cm)	205
Net weight (kg)	140
Equipment in accordance with	Directives 98/37/CE, 2006/95/CE, 2004/108/CE, 93/42/CE and following modifications
Interior of the cabinet totally free from any electrical contact that may generate a spark. Internal cabinet with shelves/drawers interchangeable.	

Accessories

Additional open wire shelf realized in sheet steel plastic coated	GSM Communicator CF2008 module
Drawer realized in aluminium	Interchange Rack System for Shelves/Baskets
Safety key locking	Internal steel wire basket
Kit of castors with brakes	Automatic water evaporation tray
PT100 sensor	Frequency 60Hz
WEB LIGHT SERVER (Rete Ethernet + GSM)	DMLP Digital Monitor (Alarm System)® Accessories for DMLP Digital Monitor® : - DMLP Printer (Graphic Temp. Printer) - DMLP Remote panel - Ext. terminal board for RS485/dry contacts - DMLP PT100 Extension module + nr.1 PT100 + 4-20mA output



At any time, the manufacturer may bring modifications to the model above described, for technical or commercial reasons. The picture does not necessary shows the product in the standard version.

