

**NEW**

**WELCH** | Formerly  
ILMVAC  
by Gardner Denver

# **C/RV**pro

*Your Robust Vacuum Pump*



**SUPPLYLAB**

GRUPO CERTILAB COMPANY

SOLUTIONS YOU CAN TRUST

T.: +351 214 278 700

F.: +351 214 278 709

[www.grupo-certilab.com](http://www.grupo-certilab.com)

[comercial@grupo-certilab.com](mailto:comercial@grupo-certilab.com)

**C/RV**pro **4,6,8,16,24,30**


APPLIED VACUUM TECHNOLOGY. ASK THE EXPERTS!

[www.welchvacuum.com/crvpro](http://www.welchvacuum.com/crvpro)

# CRVpro

## Your Robust Vacuum Pump

Discover the evolution of two-stage rotary vane vacuum pumps. Built to last. Born to perform. And designed to simplify your work. Meet the robust vacuum pump series – CRVpro.



### COOL RUNNING

Enhanced air flow allows the pump to run 10°C cooler than standard rotary vane pumps. The lower temperature leads to reduced chemical activity within the pump and slows down rates of oil consumption.

### INTERNAL SURFACE PROTECTION

Inside surface of the oil case has a PTFE coating and the outer surface of the pumping module has a black oxide coating. Both coatings act to slow metal corrosion and, when coupled with foreline traps, extend service interval.

### LARGE OIL CAPACITY

Chemical vapors that sublime from the foreline cold trap into the pump oil are more diluted due to the larger oil capacity. This minimizes the rates of oil breakdown and reduce chemical attacks within the pump.

HIGHEST RELIABILITY

LONG PRODUCT LIFESPAN

LESS MAINTENANCE

EXTENDS SERVICE INTERVAL


## YOUR BENEFITS

### Highest reliability for stable operation and long product lifespan

- ✓ Reduced risk of chemical attacks and oil breakdown by diluting chemical vapors with a larger oil chamber
- ✓ Slowing down corrosion by cool running operation
- ✓ Provides a measure of protection from sublimed chemical vapors with coating on pump module and oil case

### Extended oil change intervals for less maintenance costs

- ✓ Less oil consumption by cool running operation
- ✓ Extended usability of oil due to high dilution effect by a larger oil chamber



#### 1 LOW NOISE LEVEL

Exceptionally quiet for undisturbed work.

#### 2 FORCED OIL LUBRICATION

Ensures moving parts are bathed in fresh oil. Equilibrates temperature, minimizes oil breakdown, and prolongs mechanical life.

#### 3 ANTI-SUCK BACK VALVE

Prevents oil from being sucked into application in the event of a power failure.

#### 4 GAS BALLAST WITH INERT GAS OPTION

Minimizes entrained chemicals in pump oil. Protects pump from condensable liquids from application such as water, acetyl nitrile, etc.

#### 5 CUL AND CE CERTIFICATION

Compliance with local regulations and safety directives for safety operation.

#### 6 SIZED TO FIT YOUR APPLICATION

Modern and compact design to fit different applications and performance requirements.

#### 7 DUAL VOLTAGE MOTOR

Dual voltage motors meet IP44 standard. Motors of CRVpro 4,6,8 are switchable from 115V to 240V for global use excluding 100V and 200V pump versions. Each pump includes power cord suitable for country use.

# APPLICATIONS

SCHLENK LINE	FREEZE DRYER	VACUUM CONCENTRATOR	HVAC	VACUUM OVEN	GLOVE BOX	MASS SPECTROMETER	INDUSTRIAL APPLICATIONS
							
CRVpro 4/6	CRVpro 4/6/8	CRVpro 6	CRVpro 8	CRVpro 8	CRVpro 8/16/24/30	CRVpro 16/24/30	CRVpro 4/6/8/16/24/30

## TECHNICAL DATA

PARAMETER	UNIT	CRVpro 4	CRVpro 6	CRVpro 8	CRVpro 16	CRVpro 24	CRVpro 30
Free air displacement							
- @ 50 Hz	m³/h (L/min)	4 (67)	6 (100)	8 (133)	18,3 (305)	26,2 (436)	33,1 (551)
- @ 60 Hz	CFM (L/min)	2,8 (78)	4,2 (118)	5,6 (158)	12,8 (363)	18,3 (519)	22,1 (627)
Pumping speed							
- @ 50 Hz	m³/h (L/min)	3,8 (63)	5,1 (85)	7,3 (122)	16,8 (280)	24 (400)	29 (483)
- @ 60Hz	CFM (L/min)	2,7 (77)	3,7 (105)	5,1 (143)	11,9 (336)	17 (480)	20,5 (580)
Ultimate pressure							
- Without gas ballast partial	mbar (Torr)	5x10 <sup>-4</sup> (4x10 <sup>-4</sup> )			3x10 <sup>-4</sup> (2x10 <sup>-4</sup> )		
- Without gas ballast total	mbar (Torr)	2x10 <sup>-3</sup> (1.5x10 <sup>-3</sup> )			3x10 <sup>-3</sup> (2x10 <sup>-3</sup> )		
- With gas ballast total	mbar (Torr)	7x10 <sup>-2</sup> (5x10 <sup>-2</sup> )			6x10 <sup>-3</sup> (5x10 <sup>-3</sup> )		
Connection flanges	DN	16 KF			25 KF		
Ambient temperature	°C	10–40					
Noise level (50 Hz)	dB (A)	50			55		
Oil capacity	ml	1150		1000	2400	2200	2100
Motor speed	rpm 50/60 Hz	1450/1740			1450/1750		
Motor power	kW 50/60Hz	0,37/0,4			0,7/0,85		
Weight	kg	21	22	22,5	37	38,5	39,5
Dimensions, L x W x H	mm	463/157/230*			569/206/289		


\* Without handle

## ORDERING INFORMATION

DESCRIPTION	CRVpro 4	CRVpro 6	CRVpro 8	CRVpro 16	CRVpro 24	CRVpro 30
220-240 V / 50 Hz; 230 V / 60 Hz, 1 phase motor with line cord EU-plug (CEE 7/4), line cord UK-plug (BS1363), line cord US-plug (Nema-5)	3042-00	3062-00	3082-00	3162-00	3242-00	3302-00
Service kit	S3077-99	S3078-99	S3079-99	S3193-99	S3194-99	S3195-99
Seal kit	S3080-99			S3192-99		

Every pump is supplied complete with Directorr™ Premium vacuum pump oil, centering rings, clamping rings and motor overload protection. Ready for use after oil filling. Motor versions (e.g. explosion proof, 3-phase) upon request.

# PERFORMANCE



## COMPLETE PACKAGES & ACCESSORIES

PACKAGES (PUMP + ACCESSORIES)	DESCRIPTION	CRVpro 4	CRVpro 6	CRVpro 8
CRVpro basic package	CRVpro with oil mist separator AKD 16, 2-way ball valve, hose connector DN 16KF-10/8 mm, vacuum hose (1,5 m), oil change set	330071	330072	330073
CRVpro measurement package	CRVpro with digital vacuum gauge PIZA 111 cr-gold, oil mist separator AKD 16, 2-way ball valve, T-piece, hose connector DN16KF-10/8 mm, vacuum hose (2,5 m), oil change set	330074	330075	-

ACCESSORIES	DESCRIPTION	ORDER NO.	
		CRVpro 4,6,8	CRVpro 16,24,30
Vacuum pump oil	Directorr™ premium vacuum oil, 1 liter	800995-01	
	Directorr™ premium vacuum oil, 5 liter	800995-05	
On inlet	Inlet condenser	(AKS 16) 320016	(AKS 25) 320018
	Nitrogen (dry ice) cold trap DN10	1420H-14	-
On outlet	Oil mist separator AKD with large glass jar for easy capture and horizontal arrangement alongside the pump	(AKD 16) 320015	(AKD 25) 320017 <b>CRVpro 16 only</b>
	Economic oil mist filter OME with exchangeable cartridge (plastic)	(10/16) 700010	(25/30) 700012
	Standard exhaust filter with good capture of oil mist (metal)	1417P-8	1417P-11
	Professional exhaust filter with excellent capture of oil mist and pump noise reduction (metal)	1417C	1417D
Vacuum hose	Hose adaptor kit with hose connector, red rubber vacuum hose 1,5 m and clamps	330060	
	Stainless steel vacuum hose, 1,5 m	(DN16) 710755	(DN25) 710756
Oil change set	Oil drain valve, funnel	340011	
Application and vacuum control kit	Freeze dryer adapter kit, with oil mist separator AKD, 2-way ball valve, PVC vacuum hose (1,5 m) and hose connector DN 16KF / DN 25KF, hinge clamp ring and centering ring	(DN16) 330031	(DN25) 330032
	Vacuum control kit, digital vacuum gauge MRV 100 with PIZA 111 cr-gold, T-piece, solenoid valve, hinge clamp ring and centering ring	(DN16) 330053	(DN25) 330054

# GLOBAL CONTACT



Contact us

## EMEA

Gardner Denver Thomas GmbH  
Am Vogelherd 20  
98693 Ilmenau  
Germany

Phone: +49 3677 604 1000  
Fax: +49 3677 604131  
Email: [welch.emea@gardnerdenver.com](mailto:welch.emea@gardnerdenver.com)

## ASIA PACIFIC

Gardner Denver Welch  
Room 2206, Qiangsheng Mansion  
No. 145 Pujian Road  
200127 Shanghai  
China

Phone: +86 21 51860238  
Fax: +86 21 50396221  
Email: [welch.as@gardnerdenver.com](mailto:welch.as@gardnerdenver.com)

## AMERICA

Gardner Denver Thomas Inc.  
1601 Feehanville Drive  
Suite 550  
Mt. Prospect, IL 60056  
USA

Phone: +1 847 676 8800  
Fax: +1 847 6778606  
Email: [welch.na@gardnerdenver.com](mailto:welch.na@gardnerdenver.com)

## GLOBAL HEADQUARTERS

Gardner Denver Thomas GmbH  
Livry-Gargan-Str. 10  
82256 Fürstenfeldbruck  
Germany

Phone: +49 8141 2280 1000  
Fax: +49 8141 8892136  
Email: [welchvacuum@gardnerdenver.com](mailto:welchvacuum@gardnerdenver.com)

[www.welchvacuum.com](http://www.welchvacuum.com)  
[www.welchvacuum.de](http://www.welchvacuum.de)

**SUPPLYLAB**  
GRUPO CERTILAB COMPANY  
SOLUTIONS YOU CAN TRUST

T.: +351 214 278 700  
F.: +351 214 278 709  
[www.grupo-certilab.com](http://www.grupo-certilab.com)  
[comercial@grupo-certilab.com](mailto:comercial@grupo-certilab.com)